28 AWG FOUR COND CABLE SHIELD AND JACKETED

ELECTRI-TONE CABLE

CONSTRUCTION DETAILS

A CONDUCTOR 28 AWG 7/36 TIN PLATED COPPER
B INSULATION EXTRUDED PVC - .010" NOMINAL WALL
C DRAIN 28 AWG 7/36 TIN PLATED COPPER

D CABLE PLANETARY CABLE FOUR CONDUCTORS AND DRAIN WIRE

E SHIELD OVERALL WRAP OF ALMUMIZED MYLAR FACING IN F JACKET EXTRUDED PVC WITH NOMINAL WALL +/-.025"

COLOR - BLACK

DIAMETER(INCH) NOM. 0.015

0.015 0.033 0.015 0.071 0.075 0.125

PROPERTIES

TEMPERATURE -40°C TO 105°C

VOLTAGE 600 VOLTS RMS

FLAME RETARDANT TO VW-1


COLOR CODE

- 1 BLACK
- ₂ WHITE
- 3 RED
- 4 GREEN

PACKAGING

TO BE SUPPLIED ON 1000 FOOT REELS







THIS DRAWING IS THE PROPERTY OF THE WHITMOR/WIRENETICS COMPANY UND SHALL NOT BE REPRODUCED, COPIED, OR USED AS THE BASES FOR THE	SN		
IANUFACTURE OR SALE OF THIS DESIGN WITH OUT THE WRITTEN ERMISSION OF THE WHITMOR/WIRENETICS COMPANY	EVISION		
APPROVED BY: M. LEE			
DRAWN BY: R. SPRINKLING	꿆		

N/A

05/14/13

INITIAL RELEASE

THE LEADER IN HIGH QUALITY WIRE AND CABLE

DRAWING NO: **W- 5009-ET**

27737 AVE. HOPKINS, VALENCIA, CA 91355 PH:800-822-9473 FAX: 661-257-2495 WEB SITE: WWW.WIREANDCABLE.COM